

DLF3245 / DLH3245

31.5" TFT LCD, LED Backlight 1000nits, WXGA

31.5" is a high definition (HD) LCD panel, built-in 1000 nits high bright for sunlight readable LCD display, high transmittance color filter, high transmission polarizing plates, Low Power Consumption, suitable for kiosk, advertising, POS, marline, transportation, gaming, studio display, gas pump.

Key Features

- Sunlight Readable
- LED Backlight
- High Shock & Vibration Resistance
 Low Power Consumption
- High Uniformity
- Low EMI Noise
- Wide Dimming
- Life Expectancy (70,000hrs)



	Specifications		Preliminary	
Model No.	DLF3245	DLH3245		
Description	31.5" TFT LCD, LED Backlight 1000nits,WXGA			
Display Area (mm)	697.69 (H) x 392.26(V) mm			
Brightness	1,000 cd/m ²			
Resolution	1366 x 768 (WXGA)			
Contrast Ratio	2500 : 1			
Pixel Pitch (mm)	0.51075(H) x 0.51075(V)			
Viewing Angle	176°(H), 176°(V)			
Display Colors	16.7M colors			
Response Time (Typical)	7ms (Typical)			
Sync	LVDS			
Power Consumption	ТВА			
Dimensions (mm)	ТВА			
Weight (Net)	ТВА			
LED Driving Board	LID 32A0x			
Control Board (Optional)	AD5621GA AD5621GD AD5766	GDVA □AD266	52GDVAR	
AD5621GA	VGA+Audio			
AD5621GD	VGA+DVI			
AD2662GDVAR	VGA+DVI (Optional S-Video/ Component / Audio)			
F / R Control Button	5 Key4 Key			
5 Key	Power Switch, Menu, Select (+,-), Auto			
4 Key	Power Switch, Menu, Select (+,-),			
OSD Menu	Brightness, Contrast, H/V Position, Color, Phase, Clock			
Optional	AOT Touch Screen			

Specifications are subject to change without notice.

All brands or product names are trademarks or registered trademarks of their respective companies.

DLF= Panel+LED Driving Board

DLH = Panel+LED Driving Board+Control Board

2010/6/14 1



Mechanical Drawing

Outline Dimensions

Unit:mm

Ordering Information			
Model Name	Description		
	Optional Accessories		
Part Number	Description		
		-	

2 2010/6/14