



SLO3245 TFT LCD, LED Backlight 1000nits

SLO3245 is a high definition (HD) LCD panel, built-in 1000 nits high bright for sunlight readable LCD display, high transmittance color filter, high transmission polarizing plates, Low Power Consumption, suitable for kiosk, advertising, POS, marline, transportation, gaming, studio display, gas pump.

Key Features

- Sunlight Readable
- LED Backlight
- High Shock & Vibration Resistance
- Low Power Consumption
- High Uniformity
- Low EMI Noise
- Wide Dimming
- Life Expectancy



Specifications

Preliminary

Model No.	SLO3245
Description	32" TFT LCD, LED Backlight 1000nits
Display Area (mm)	697.7 (H) x 392.3(V) mm
Brightness	1,000 cd/m ²
Resolution	1366 x 768
Contrast Ratio	2500 : 1
Pixel Pitch (mm)	0.51(H) x 0.51(V)
Viewing Angle	176°(H), 176°(V)
Display Colors	16.7M colors
Response Time (Typical)	7ms (Typical)
Sync	LVDS
Power Input	DC-12V
Power Consumption	81W
Dimensions (mm)	788.8x340x62mm
Weight (Net)	9Kg
Operation Temp.	0 ~ 50 °C
LED Driving Board	LID 32
Control Board	<input type="checkbox"/> AD5621GA <input type="checkbox"/> AD5621GD <input type="checkbox"/> AD5766GDVA <input type="checkbox"/> AD2662GDVAR
<input type="checkbox"/> AD5621GA	VGA+Audio
<input type="checkbox"/> AD5621GD	VGA+DVI
<input type="checkbox"/> AD5766GDVA	VGA+CVBS+S-Video+Audio (Optional DVI / Component)
<input type="checkbox"/> AD2662GDVAR	VGA+DVI (Optional S-Video/ Component / Audio)
F / R Control Button	<input type="checkbox"/> 4 Key
<input type="checkbox"/> 4 Key	Power Switch, Menu, Select (+,-),
OSD Menu	Brightness, Contrast, H/V Position, Color, Phase, Clock...
Light Sensor	0.5nits ~ 1000nits

Specifications are subject to change without notice.

All brands or product names are trademarks or registered trademarks of their respective companies.



Mechanical Drawing

Outline Dimensions

